

ROTAX® ENGINE	600 ACE
Engine details	Liquid-cooled, four-stroke D.O.H.C.
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters

Viper Red/Black	
3060 mm	
1280 mm	
1470 mm	
1080 mm	
381 mm	
3487 mm	
34 mm Cobra	

POWERTRAIN

Drive clutch type	eDrive II
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS3-3500
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien-X
Skis	Blade DS+
Seating	2-up
Handlebar	Steel with hooks
Riser block height	120 mm
Starter	Electric
Reverse	Mechanical
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Windshield	Extra high with side deflectors
Visor Plug front / rear	Front
USB power outlet	Yes, in front compartment
Air radiator with fan	Yes
LinQ attachment	1 pair

^{*} Vehicle overall length without snowflap.